SAFETY DATA SHEET



1. Identification

Product identifier	PELLETIZED GYPSUM EQUIVALENT (CA) FINE
Other means of identification	None.
Recommended use	Ag Product - Plant Nutrition
Recommended restrictions	Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

Manufacturer			
Company name	Wilbur-Ellis Company LLC		
Address	16300 Christensen Rd. Ste 135		
	Tukwila, WA 98188		
	United States		
Telephone	Branded Products Information	(800) 500-1698	
E-mail	SDS@wilburellis.com		
Emergency phone number	Chemtrec - Domestic	(800) 424-9300	
	Chemtrec - International	+1 703-741-5970	

Manufacturer/Importer/Supplier/Distributor information

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Carcinogenicity	Category 1A
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	May cause cancer.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If exposed or concerned: Get medical advice/attention.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Calcium Sulfate		7778-18-9	90 - 100
Crystalline Silica (Quartz)		14808-60-7	< 0.2
Other components below re	eportable levels		3 - < 5

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately.
Most important symptoms/effects, acute and delayed	Dusts may irritate the respiratory tract, skin and eyes.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	

Suitable extinguishing media Unsuitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Use water spray to cool unopened containers.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Avoid the generation of dusts during clean-up. Collect dust using a vacuum cleaner equipped with HEPA filter. Stop the flow of material, if this is without risk.
	Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water.
	Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)			
Components	Туре	Value	Form
Calcium Sulfate (CAS 7778-18-9)	PEL	5 mg/m3	Respirable fraction.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type

Components	Type	Value	Form
		15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CF Components	-R 1910.1000) Туре	Value	Form
Crystalline Silica (Quartz) (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limi			
Components	Туре	Value	Form
Calcium Sulfate (CAS 7778-18-9)	TWA	10 mg/m3	Inhalable fraction.
Crystalline Silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide	to Chemical Hazards		
Components	Туре	Value	Form
Calcium Sulfate (CAS 7778-18-9)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Crystalline Silica (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
logical limit values	No biological exposure limits noted for the	ingredient(s).	
oosure guidelines	Occupational exposure to nuisance dust (should be monitored and controlled.	total and respirable) and re	espirable crystalline silica
propriate engineering ntrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits.		
ividual protection measures	s, such as personal protective equipment		
Eye/face protection	Chemical respirator with organic vapor car	rtridge, full facepiece, dust	and mist filter.
Skin protection Hand protection	Wear appropriate chemical resistant glove	es.	
Other	Wear suitable protective clothing. Use of a	an impervious apron is reco	ommended.
Respiratory protection	Use a NIOSH/MSHA approved respirator i exceeding the exposure limits. Chemical r dust and mist filter.	if there is a risk of exposur	e to dust/fume at levels
Thermal hazards	Wear appropriate thermal protective clothi	ng, when necessary.	
neral hygiene nsiderations	Observe any medical surveillance requirer measures, such as washing after handling smoking. Routinely wash work clothing ar	the material and before ea	ating, drinking, and/or
Physical and chemical	properties		
pearance	White to tan powder.		
pour arrow			

Appearance	while to tall powder
Physical state	Solid.
Form	Powder.
Color	White to tan.
Odor	Odorless.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.

Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Aluminum. Phosphorus.
Hazardous decomposition products	No hazardous decomposition products are known.
11. Toxicological informat	ion
Information on likely routes of e	xposure
Inhalation	Dust may irritate respiratory system. Prolonged inhalation may be harmful.
Skin contact	Dust or powder may irritate the skin.

Innalation	Dust may imitate respiratory system. Prolonged innalation may be narm
Skin contact	Dust or powder may irritate the skin.
Eye contact	Dust may irritate the eyes.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Dusts may irritate the respiratory tract, skin and eyes.

Information on toxicological effects

Acute toxicity	Not known.	
Components	Species	Test Results
Calcium Sulfate (CAS 77	78-18-9)	
<u>Acute</u>		
Inhalation		
Dust		
LC50	Rat	> 3.26 mg/l, 4 Hours

Components	Species	Test Results
Oral	- /	
LD50	Rat	> 1581 mg/kg
Skin corrosion/irritation	Prolonged skin contact may	cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may	y cause temporary irritation.
Respiratory or skin sensitizatio	n	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate mutagenic or genotoxic.	product or any components present at greater than 0.1% are
Carcinogenicity	inhaled from occupational so overall evaluation, IARC not circumstances studied. Carc crystalline silica or on extern polymorphs." (IARC Monog humans, Silica, silicates dus 2003, SCOEL (the EU Scien main effect in humans of the sufficient information to cond silicosis (and, apparently, no in the ceramic industry). Th risk" (SCOEL SUM Doc 94 protection against silicosis c occupational exposure limits respirable crystalline silica s	bonal Agency for Research on Cancer) concluded that crystalline silical bources can cause lung cancer in humans. However in making the ed that "carcinogenicity was not detected in all industrial binogenicity may be dependent on inherent characteristics of the hal factors affecting its biological activity or distribution of its raphs on the evaluation of the carcinogenic risks of chemicals to but and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June notific Committee on Occupational Exposure Limits) concluded that the e inhalation of respirable crystalline silica dust is silicosis. "There is clude that the relative risk of lung cancer is increased in persons with bot in employees without silicosis exposed to silica dust in quarries and erefore, preventing the onset of silicosis will also reduce the cancer 4-final, June 2003) According to the current state of the art, worker an be consistently assured by respecting the existing regulatory 6. May cause cancer. Occupational exposure to respirable dust and hould be monitored and controlled.
	Evaluation of Carcinogenicit	У
Not regulated.	d Substances (29 CFR 1910. ogram (NTP) Report on Carc	
Reproductive toxicity		to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects		e harmful. Prolonged exposure may cause chronic effects.
12. Ecological informatior Ecotoxicity	The product is not classified	as environmentally hazardous. However, this does not exclude the ent spills can have a harmful or damaging effect on the environment
Persistence and degradability		degradability of any ingredients in the mixture.
Bioaccumulative potential	No data available.	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environme	ental effects (e.g. ozone depletion, photochemical ozone creation on, global warming potential) are expected from this component.
13. Disposal consideration	ns	
Disposal instructions		se in sealed containers at licensed waste disposal site. Dispose of lance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with	all applicable regulations.
Hazardous waste code	The waste code should be a disposal company.	ssigned in discussion between the user, the producer and the waste

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are listed on or exempted from the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes chemical

Classified hazard Carcinogenicity categories

SARA 313 (TRI reporting) Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated. (SDWA)

US state regulations

California Proposition 65

WARNING: This product can expose you to Crystalline Silica (Quartz), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline Silica (Quartz) (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3,

subd. (a))

Crystalline Silica (Quartz) (CAS 14808-60-7)

16. Other information, including date of preparation or last revision

Issue date	04-25-2019
Version #	01

NFPA ratings

NFPA ratings

Health: 0 Flammability: 0 Instability: 0



Disclaimer

This information was developed from information on the constituent materials. No warranty is expressed or implied regarding the completeness or continuing accuracy of the information contained herein, and Wilbur-Ellis Company LLC disclaims all liability for reliance thereon. The user should satisfy himself that he has all current data relevant to his particular use.