

MATERIAL SAFETY DATA SHEET

TAZER

1. **CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**
REAL FARM TECHNOLOGIES, LLC
605 12th Street
Aurora, NE 68818

PRODUCT NAME: TAZER

EPA REG. NO.: Not Applicable

CHEMICAL NAME: Modified Vegetable Oil & Organosilicone Surfactant

CHEMICAL FAMILY: Adjuvant

Hotline Numbers: For Chemical Emergency, Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night
Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2. HAZARDS IDENTIFICATION SUMMARY

KEEP OUT OF REACH OF CHILDREN – CAUTION: Causes moderate eye irritation. Harmful if swallowed, inhaled or absorbed through skin. Avoid contact with eyes, skin or clothing. Wash thoroughly after handling. In case of contact, wash skin with soap and water; for eyes, flush with water for 15 minutes and get medical attention.

3. COMPOSITION, INFORMATION ON INGREDIENTS

<u>Chemical Ingredients:</u>	<u>Percentage by Weight:</u>	<u>CAS No.</u>	<u>TLV (Units)</u>
Modified Vegetable Oil, Organosilicone and Non-Ionic Emulsifiers	99	Mixture	Not listed
Constituents ineffective as spray adjuvant	1	Not listed	Not listed

4. FIRST AID MEASURES

If in Eyes: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes then continue rinsing eye. Call a poison control center or doctor for treatment advice.

If on Skin or Clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

If Swallowed: Immediately call a poison control center or doctor. Do not induce vomiting unless told to do so by the poison control center or doctor. Have person sip a glass of water if able to swallow. Do not give anything by mouth to an unconscious person.

If Inhaled: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for treatment advice.

FOR A MEDICAL EMERGENCY INVOLVING THIS PRODUCT have the product container or label with you when calling a poison control center or doctor.

5. FIRE FIGHTING MEASURES

FLASH POINT (^oF/Test Method): >200°F

FLAMMABLE LIMITS (LFL & UFL): Not established

EXTINGUISHING MEDIA: Use foam, dry chemical, carbon dioxide, water spray or fog.

HAZARDOUS COMBUSTION PRODUCTS: Toxic fumes may be emitted in a fire situation.

SPECIAL FIRE FIGHTING PROCEDURES: Evacuate area and fight fire upwind from a safe distance to avoid hazardous vapors and decomposition products. Fire exposed containers can build up pressure and should be kept cool with water spray if possible. Explosive vapor could form from ruptured containers. Dike and collect water used to fight fire to prevent environmental damage due to run off. Foam or dry chemical fire extinguishing systems are preferred to prevent environmental damage from excessive water runoff.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Can burn in fire, releasing irritating and toxic gases due to thermal decomposition or combustion.

FIRE FIGHTING EQUIPMENT: Self-contained breathing apparatus with full facepiece. Full fire fighting turn-out gear (Bunker gear).

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: In case of leak or spill, contain material and dispose as waste. Do not contaminate any body of water. Pick up spilled liquid with absorbent material and sweep up for disposal. Place it and damaged unusable containers in a landfill appropriate for non hazardous chemical waste. Check local, state and federal regulations for proper disposal. **NOTE:** Prevent spilled material from flowing onto adjacent land, or into municipal sewers and open bodies of water. Always wear proper protective equipment when working with the product.

MATERIAL SAFETY DATA SHEET

TAZER

7. HANDLING AND STORAGE

HANDLING: Wash hands after handling, and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing.

STORAGE: Store in a cool, dry place away from children and animals. Mix well before using. Keep tightly closed. Do not contaminate water, foodstuffs, feed or seed by storage or disposal.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION: If needed, use MSHA-NIOSH approved respirator for organic vapors.

EYE PROTECTION: Wear chemical goggles or shielded safety glasses when handling and mixing product.

SKIN PROTECTION: Wear protective clothing: long-sleeved shirts and pants, shoes plus socks and chemical-resistant gloves. Always refer to the label of the pesticide(s) in the tank mix and follow the most restrictive requirements.

Personal Protective Equipment (PPE): Eye protection, long sleeved shirt and long pants, shoes plus socks and chemical resistant gloves. Follow manufacturer's instructions for cleaning/maintaining PPE. If not such instructions for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear, pale yellow liquid, Fatty

SOLUBILITY: Dispersible **pH:** ~7 (1% Sol)

SPECIFIC GRAVITY (Water=1): 0.895 – 0.915g/ml

BULK DENSITY: 7.46 – 7.63 lbs/gal.

VAPOR PRESSURE: Not established

BOILING POINT: Not established

PERCENT VOLATILE (by volume): Not Applicable

EVAPORATION RATE: Not established

Note: These physical data are typical values based on material tested but may vary from sample to sample.

Typical values should not be construed as a guaranteed analysis of any specific lot or as specification items.

10. STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: Prolonged elevated temperatures.

IMCOMPATIBILITY: Avoid strong acids, gases and oxidizers.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: May emit toxic fumes if excessively heated.

11. TOXICOLOGICAL INFORMATION – Not Available

Acute Oral LD₅₀:

Acute Dermal LD₅₀:

Eye Irritation:

Skin Irritation:

Inhalation LC₅₀:

Skin sensitization:

Carcinogenic Potential: None listed in OSHA, NTP, IARC, or ACGIH

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL SUMMARY: This product not labeled for use in aquatic sites.

13. DISPOSAL CONSIDERATIONS

Do not reuse product containers. Triple rinse (or equivalent), then offer for recycling at an ACRC site (go to <http://www.acrecycle.org> for locations) or by reconditioning, or puncture and dispose of in a sanitary landfill or by other procedures approved by local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT SHIPPING DESCRIPTION: Not regulated

DOT HAZARD CLASS: None

UN NUMBER: None

DOT PACKING GROUP: None

DOT PRIMARY/SECONDARY LABEL: None

DOT PRIMARY/SECONDARY PLACARD: None

15. REGULATORY INFORMATION

NFPA RATINGS: Least = 0 Slight = 1 Moderate = 2 High = 3 Severe = 4

Ratings for this product: Health – 1 Flammability – 0 Instability – 0 Special Hazards – None Specified

MATERIAL SAFETY DATA SHEET

TAZER

SARA Title III Hazard Category: Immediate Y Fire N Sudden Release of Pressure N
Delayed N Reactive N

Reportable Quantity (RQ) under U.S. CERCLA:

Chemical Name	CAS Number	Range in %	RQ
Glycol ethers (fraction of product matching EPA definition)	Mixture	0.9-1.8	1
Residual ethylene oxide (typical)	75-21-8	<0.001	10

SARA, Title III, Section 313: Not Listed

CA Proposition 65:

WARNING! This product may contain a detectable amount of ethylene oxide, which is known to the State of California to cause cancer and/or reproductive toxicity. Ethoxylated products may contain residual amounts of ethylene oxide (EO) which can accumulate in the container headspace and be released into the ambient environment. This process is enhanced when the product is agitated, as during tank car loading and unloading, and blending operations. Ethylene oxide causes tumors in laboratory animals. The Occupational Safety and Health Administration (OSHA) Permissible Exposure Level (PEL) for EO is 1 ppm for an eight-hour time weighted average exposure. The standard regulates occupational exposure to EO from all sources, including products containing residual EO. It is the responsibility of the employer to comply with OSHA ethylene oxide standard (29) CFR 1910.1047). Ethylene oxide <0.001

16. OTHER

Date of Issue: 03/28/2013 Supersedes: New

Disclaimer and Limitation of Liability: This data sheet was developed from information on the constituent materials identified herein and does not relate to the use of such materials in combination with any other material or process. No warranty is expressed or implied with respect to the completeness or ongoing accuracy of the information contained in this data sheet, and Real Farm Technologies, LLC, disclaims all liability for reliance on such information. This data sheet is not a guarantee of safety. Users are responsible for ensuring that they have all current information necessary to safely use the product described by this data sheet for their specific purpose.