

**TILT**

Version 2.0	Revision Date: 04/03/2023	SDS Number: S11303321	This version replaces all previous versions.
----------------	------------------------------	--------------------------	--

**SECTION 1. IDENTIFICATION**

Product name : TILT  
Design code. : A6140A  
  
Product Registration number : 100-617

**Manufacturer or supplier's details**

Company name of supplier : Syngenta Crop Protection, LLC  
Address : Post Office Box 18300  
Greensboro NC 27419  
United States of America (USA)

Telephone : 1 800 334 9481  
Telefax : 1 336 632 2192

E-mail address : sds.requests@syngenta.com  
Emergency telephone : 1 800 888 8372

**Recommended use of the chemical and restrictions on use**

Recommended use : Fungicide  
  
Restrictions on use : General Use Pesticide

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Flammable liquids : Category 3  
  
Acute toxicity (Oral) : Category 4  
  
Acute toxicity (Inhalation) : Category 4  
  
Skin irritation : Category 2  
  
Eye irritation : Category 2A  
  
Skin sensitization : Category 1  
  
Carcinogenicity : Category 2  
  
Reproductive toxicity : Category 2  
  
Specific target organ toxicity : Category 3 (Respiratory system)  
- single exposure  
  
Specific target organ toxicity : Category 2 (Central nervous system, Kidney, Liver, hearing  
- repeated exposure organs)  
  
Aspiration hazard : Category 1

**TILT**Version  
2.0Revision Date:  
04/03/2023SDS Number:  
S11303321

This version replaces all previous versions.

**GHS label elements**

Hazard pictograms

:



Signal Word

:

Danger

Hazard Statements

:

H226 Flammable liquid and vapor.  
H302 + H332 Harmful if swallowed or if inhaled.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H351 Suspected of causing cancer.  
H361d Suspected of damaging the unborn child.  
H373 May cause damage to organs (Central nervous system, Kidney, Liver, hearing organs) through prolonged or repeated exposure.

Precautionary Statements

:

**Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe mist or vapors.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/

**TILT**Version  
2.0Revision Date:  
04/03/2023SDS Number:  
S11303321

This version replaces all previous versions.

attention.

P331 Do NOT induce vomiting.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
solvent naphtha (petroleum), light arom.	64742-95-6	$\geq 30 - < 50$
propiconazole	60207-90-1	41.5534
1,2,4-trimethyl-benzene	95-63-6	$\geq 10 - < 20$
xylene mixture of isomers	1330-20-7	$\geq 10 - < 20$
ethyl benzene	100-41-4	$\geq 5 - < 10$
toluene	108-88-3	$\geq 0.1 - < 1$

Actual concentration is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

- General advice : Have the product container, label or Safety Data Sheet with you when calling the emergency number, a poison control center or physician, or going for treatment.
- If inhaled : Take the victim into fresh air.  
If breathing is irregular or stopped, administer artificial respiration.  
Keep patient warm and at rest.  
Call a physician or poison control center immediately.
- In case of skin contact : Take off all contaminated clothing immediately.  
Wash off immediately with plenty of water.  
If skin irritation persists, call a physician.  
Wash contaminated clothing before re-use.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

**TILT**

Version 2.0	Revision Date: 04/03/2023	SDS Number: S11303321	This version replaces all previous versions.
----------------	------------------------------	--------------------------	--

- |   |   |
|---|---|
|   | for at least 15 minutes.<br>Remove contact lenses.<br>Immediate medical attention is required.  |
| If swallowed  | : If swallowed, seek medical advice immediately and show this container or label.<br>Do not induce vomiting: contains petroleum distillates and/or aromatic solvents. |
| Most important symptoms and effects, both acute and delayed | : Aspiration may cause pulmonary edema and pneumonitis.   |
| Notes to physician  | : There is no specific antidote available.<br>Treat symptomatically.<br>Do not induce vomiting: contains petroleum distillates and/or aromatic solvents.              |

**SECTION 5. FIRE-FIGHTING MEASURES**

- |  |  |
|--|--|
| Suitable extinguishing media                   | : Extinguishing media - small fires<br>Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.<br>Extinguishing media - large fires<br>Alcohol-resistant foam   |
| Unsuitable extinguishing media                 | : Do not use a solid water stream as it may scatter and spread fire.   |
| Specific hazards during fire fighting          | : As the product contains combustible organic ingredients, fire will produce dense black smoke containing hazardous products of combustion (see section 10).<br>Exposure to decomposition products may be a hazard to health.<br>Flash back possible over considerable distance. |
| Further information                            | : Do not allow run-off from fire fighting to enter drains or water courses.<br>Cool closed containers exposed to fire with water spray.  |
| Special protective equipment for fire-fighters | : Wear full protective clothing and self-contained breathing apparatus.  |

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- |   |  |
|---|--|
| Personal precautions, protective equipment and emergency procedures | : Refer to protective measures listed in sections 7 and 8.<br>Keep people away from and upwind of spill/leak.<br>Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.<br>Remove all sources of ignition.<br>Pay attention to flashback. |
| Environmental precautions   | : Prevent further leakage or spillage if safe to do so.<br>Do not flush into surface water or sanitary sewer system.<br>If the product contaminates rivers and lakes or drains inform respective authorities.  |
| Methods and materials for containment and cleaning up               | : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).<br>Clean contaminated surface thoroughly.            |

**TILT**Version  
2.0Revision Date:  
04/03/2023SDS Number:  
S11303321

This version replaces all previous versions.

Clean with detergents. Avoid solvents.  
Retain and dispose of contaminated wash water.

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling : Avoid contact with skin and eyes.  
When using do not eat, drink or smoke.  
Use only in an area containing flame proof equipment.  
Take precautionary measures against static discharges.  
For personal protection see section 8.
- Conditions for safe storage : Keep containers tightly closed in a dry, cool and well-ventilated place.  
Keep out of the reach of children.  
Keep away from combustible material.  
Keep in an area equipped with sprinklers.  
Keep away from food, drink and animal feedingstuffs.  
No smoking.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
solvent naphtha (petroleum), light arom.	64742-95-6	TWA	500 ppm 2,000 mg/m <sup>3</sup>	OSHA Z-1
		TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	ACGIH
propiconazole	60207-90-1	TWA	5 mg/m <sup>3</sup>	Syngenta
1,2,4-trimethyl-benzene	95-63-6	TWA	25 ppm 125 mg/m <sup>3</sup>	NIOSH REL
		TWA	25 ppm	ACGIH
		TWA	25 ppm 125 mg/m <sup>3</sup>	OSHA P0
		TWA	10 ppm	ACGIH
xylene mixture of isomers	1330-20-7	TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA Z-1
		TWA	20 ppm	ACGIH
		STEL	150 ppm 655 mg/m <sup>3</sup>	OSHA P0
		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA P0
ethyl benzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m <sup>3</sup>	NIOSH REL
		ST	125 ppm 545 mg/m <sup>3</sup>	NIOSH REL
		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA Z-1
		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA P0
		STEL	125 ppm	OSHA P0

**TILT**Version  
2.0Revision Date:  
04/03/2023SDS Number:  
S11303321

This version replaces all previous versions.

			545 mg/m <sup>3</sup>	
toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m <sup>3</sup>	NIOSH REL
		ST	150 ppm 560 mg/m <sup>3</sup>	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm (10 minutes)	OSHA Z-2
		TWA	100 ppm 375 mg/m <sup>3</sup>	OSHA P0
		STEL	150 ppm 560 mg/m <sup>3</sup>	OSHA P0

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
xylene mixture of iso-mers	1330-20-7	Methylhippu-ric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
ethyl benzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI
toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g creatinine	ACGIH BEI

**Engineering measures** : THE FOLLOWING RECOMMENDATIONS FOR EXPOSURE CONTROLS/PERSONAL PROTECTION ARE INTENDED FOR THE MANUFACTURE, FORMULATION AND

**TILT**Version  
2.0Revision Date:  
04/03/2023SDS Number:  
S11303321

This version replaces all previous versions.

PACKAGING OF THE PRODUCT. FOR COMMERCIAL APPLICATIONS AND/OR ON-FARM APPLICATIONS CONSULT THE PRODUCT LABEL.

Containment and/or segregation is the most reliable technical protection measure if exposure cannot be eliminated. The extent of these protection measures depends on the actual risks in use.

Maintain air concentrations below occupational exposure standards.

Where necessary, seek additional occupational hygiene advice.

**Personal protective equipment**

Respiratory protection : Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Remarks : Wear protective gloves. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The breakthrough time depends amongst other things from the material, the thickness and the type of glove and therefore has to be measured for each case. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection : Tightly fitting safety goggles  
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.  
Remove and wash contaminated clothing before re-use.  
Wear as appropriate:

Protective measures : Impervious clothing  
The use of technical measures should always have priority over the use of personal protective equipment.  
When selecting personal protective equipment, seek appropriate professional advice.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**TILT**Version  
2.0Revision Date:  
04/03/2023SDS Number:  
S11303321

This version replaces all previous versions.

Appearance	:	clear, liquid
Color	:	amber
Odor	:	aromatic, like solvent
Odor Threshold	:	No data available
pH	:	4 - 7 (77 °F / 25 °C) Concentration: 1 %w/v
Melting point/range	:	No data available
Boiling point/boiling range	:	356 °F / 180 °C
Flash point	:	111 °F / 44 °C  Method: Pensky-Martens closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Density	:	1.03 g/cm <sup>3</sup> (68 - 77 °F / 20 - 25 °C)
Solubility(ies) Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	869 °F / 465 °C
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	No data available



**TILT**Version  
2.0Revision Date:  
04/03/2023SDS Number:  
S11303321

This version replaces all previous versions.

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	None reasonably foreseeable.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	No dangerous reaction known under conditions of normal use.
Conditions to avoid	:	No decomposition if used as directed.
Incompatible materials	:	None known.
Hazardous decomposition products	:	No hazardous decomposition products are known.

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Ingestion  
Inhalation  
Skin contact  
Eye contact

**Acute toxicity****Product:**

Acute oral toxicity	:	LD50 (Rat, female): 1,100 mg/kg
Acute inhalation toxicity	:	LC50 (Rat, male and female): > 2.45 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance/mixture is not toxic on inhalation as defined by dangerous goods regulations.
Acute dermal toxicity	:	LD50 (Rabbit, male and female): > 5,010 mg/kg

**Components:****propiconazole:**

Acute oral toxicity	:	LD50 (Rat, female): 550 mg/kg
Acute inhalation toxicity	:	LC50 (Rat, male and female): > 5.8 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	:	LD50 (Rat, male and female): > 5,000 mg/kg

**1,2,4-trimethyl-benzene:**

Acute inhalation toxicity	:	Assessment: The component/mixture is moderately toxic after short term inhalation.
---------------------------	---	--

**xylene mixture of isomers:**

Acute oral toxicity	:	LD50 (Rat, female): 3,523 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 27.124 mg/l

**TILT**Version  
2.0Revision Date:  
04/03/2023SDS Number:  
S11303321

This version replaces all previous versions.

Exposure time: 4 h  
Test atmosphere: vapor**ethyl benzene:**

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

**Skin corrosion/irritation****Product:**Species : Rabbit  
Result : Irritating to skin.**Components:****propiconazole:**Species : Rabbit  
Result : No skin irritation**1,2,4-trimethyl-benzene:**

Assessment : Irritating to skin.

**xylene mixture of isomers:**

Result : Irritating to skin.

**toluene:**Species : Rabbit  
Result : Irritating to skin.**Serious eye damage/eye irritation****Product:**Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days**Components:****propiconazole:**Species : Rabbit  
Result : No eye irritation**1,2,4-trimethyl-benzene:**

Assessment : Irritating to eyes.

**xylene mixture of isomers:**

Result : Eye irritation

**TILT**Version  
2.0Revision Date:  
04/03/2023SDS Number:  
S11303321

This version replaces all previous versions.

**Respiratory or skin sensitization****Product:**

Species : Guinea pig  
Result : May cause sensitization by skin contact.

**Components:****propiconazole:**

Species : Guinea pig  
Result : The product is a skin sensitizer, sub-category 1B.

**Germ cell mutagenicity****Components:****propiconazole:**

Germ cell mutagenicity - Assessment : Animal testing did not show any mutagenic effects.

**Carcinogenicity****Components:****propiconazole:**

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

**IARC** Group 2B: Possibly carcinogenic to humans  
ethyl benzene 100-41-4

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity****Components:****propiconazole:**

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

**toluene:**

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

**TILT**Version  
2.0Revision Date:  
04/03/2023SDS Number:  
S11303321

This version replaces all previous versions.

**STOT-single exposure****Components:****propiconazole:**

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

**1,2,4-trimethyl-benzene:**

Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

**xylene mixture of isomers:**

Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

**toluene:**

Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

**STOT-repeated exposure****Components:****propiconazole:**

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

**xylene mixture of isomers:**

Target Organs : Central nervous system, Kidney, Liver  
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

**ethyl benzene:**

Target Organs : hearing organs  
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

**toluene:**

Target Organs : Central nervous system  
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

**TILT**Version  
2.0Revision Date:  
04/03/2023SDS Number:  
S11303321

This version replaces all previous versions.

**Aspiration toxicity****Components:****solvent naphtha (petroleum), light arom.:**

May be fatal if swallowed and enters airways.

**1,2,4-trimethyl-benzene:**

May be fatal if swallowed and enters airways.

**xylene mixture of isomers:**

May be fatal if swallowed and enters airways.

**ethyl benzene:**

May be fatal if swallowed and enters airways.

**toluene:**

May be fatal if swallowed and enters airways.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****propiconazole:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.3 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Americamysis): 0.51 mg/l  
aquatic invertebrates Exposure time: 96 h

Toxicity to algae/aquatic : ErC50 (Raphidocelis subcapitata (freshwater green alga)): 8.9  
plants mg/l  
Exposure time: 96 h  
  
EC10 (Raphidocelis subcapitata (freshwater green alga)):  
0.96 mg/l  
End point: Growth rate  
Exposure time: 72 h

Toxicity to fish (Chronic tox- : NOEC (Cyprinodon variegatus (sheepshead minnow)): 0.068  
icity) mg/l  
Exposure time: 95 d

Toxicity to daphnia and other : NOEC (Americamysis): 0.11 mg/l  
aquatic invertebrates (Chron- Exposure time: 28 d  
ic toxicity)

Toxicity to microorganisms : EC50 (activated sludge): > 100 mg/l  
Exposure time: 3 h

**TILT**Version  
2.0Revision Date:  
04/03/2023SDS Number:  
S11303321

This version replaces all previous versions.

**Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

**1,2,4-trimethyl-benzene:**Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 7.72 mg/l  
Exposure time: 96 hToxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 3.6 mg/l  
aquatic invertebrates Exposure time: 48 h**Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**xylene mixture of isomers:**Toxicity to algae/aquatic : EC50: 2.2 mg/l  
plants Exposure time: 72 hNOEC: 0.44 mg/l  
Exposure time: 72 h**ethyl benzene:**Toxicity to fish : LC50 (Marine species): 5.1 mg/l  
Exposure time: 96 hToxicity to daphnia and other : EC50 (Mysidopsis bahia (opossum shrimp)): 2.6 mg/l  
aquatic invertebrates Exposure time: 96 hToxicity to daphnia and other : NOEC (Ceriodaphnia dubia (Water flea)): 0.96 mg/l  
aquatic invertebrates (Chronic toxicity) Exposure time: 7 d**toluene:**Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5.5 mg/l  
Exposure time: 96 hToxicity to daphnia and other : EC50 (Ceriodaphnia dubia (water flea)): 3.78 mg/l  
aquatic invertebrates Exposure time: 48 h**Persistence and degradability****Components:****propiconazole:**

Biodegradability : Result: Not readily biodegradable.

**xylene mixture of isomers:**

Biodegradability : Result: Readily biodegradable.

**ethyl benzene:**

Biodegradability : Result: Readily biodegradable.

**TILT**Version  
2.0Revision Date:  
04/03/2023SDS Number:  
S11303321

This version replaces all previous versions.

**toluene:**

Biodegradability : Result: Readily biodegradable.

**Bioaccumulative potential****Components:****propiconazole:**

Bioaccumulation : Remarks: Medium bioaccumulation potential.

Partition coefficient: n-octanol/water : log Pow: 3.72 (77 °F / 25 °C)

**toluene:**

Bioaccumulation : Remarks: Does not bioaccumulate.

**Mobility in soil****Components:****propiconazole:**

Distribution among environmental compartments : Remarks: Low to medium mobility in soil.

Stability in soil : Dissipation time: 66 - 170 d  
Percentage dissipation: 50 % (DT50)  
Remarks: Product is not persistent.**Other adverse effects****Components:****propiconazole:**

Results of PBT and vPvB assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

**toluene:**

Results of PBT and vPvB assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**RCRA - Resource Conservation and Recovery Authorization Act  
Waste Code:  
:  
: D001: Ignitability

Waste from residues

: Do not contaminate ponds, waterways or ditches with chemical or used container.  
Do not dispose of waste into sewer.  
Where possible recycling is preferred to disposal or

**TILT**

Version 2.0	Revision Date: 04/03/2023	SDS Number: S11303321	This version replaces all previous versions.
----------------	------------------------------	--------------------------	--

incineration.  
If recycling is not practicable, dispose of in compliance with local regulations.

Contaminated packaging : Empty remaining contents.  
Triple rinse containers.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Do not re-use empty containers.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(XYLENES, ETHYL BENZENE)  
Class : 3  
Packing group : III  
Labels : 3

**IATA-DGR**

UN/ID No. : UN 1993  
Proper shipping name : Flammable liquid, n.o.s.  
(XYLENES, ETHYL BENZENE)  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(XYLENES, ETHYL BENZENE)  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : yes

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

UN/ID/NA number : UN 1993  
Proper shipping name : Flammable liquids, n.o.s.  
(XYLENES, ETHYL BENZENE)  
Class : 3  
Packing group : III  
Labels : FLAMMABLE LIQUID  
ERG Code : 128  
Marine pollutant : no



**TILT**Version  
2.0Revision Date:  
04/03/2023SDS Number:  
S11303321

This version replaces all previous versions.

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**SECTION 15. REGULATORY INFORMATION**

This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label:

**Warning**

Causes substantial but temporary eye injury.

Harmful if swallowed.

Harmful if inhaled.

Harmful if absorbed through skin.

Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

Avoid breathing spray mist.

May cause skin sensitization reactions in certain individuals.

Do not get in eyes, on skin, or on clothing.

Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet.

**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylene mixture of isomers	1330-20-7	100	719

A characteristic waste RQ of 100 lbs applies to this product in a waste form: D001

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards**

: Flammable (gases, aerosols, liquids, or solids)  
 Acute toxicity (any route of exposure)  
 Respiratory or skin sensitization  
 Carcinogenicity  
 Reproductive toxicity  
 Specific target organ toxicity (single or repeated exposure)  
 Aspiration hazard  
 Skin corrosion or irritation  
 Serious eye damage or eye irritation

**SARA 313**


: The following components are subject to reporting levels established by SARA Title III, Section 313:

propiconazole	60207-90-1	>= 30 - < 50 %
1,2,4-trimethylbenzene	95-63-6	>= 10 - < 20 %

**TILT**Version  
2.0Revision Date:  
04/03/2023SDS Number:  
S11303321

This version replaces all previous versions.

xylylene mixture of isomers	1330-20-7	>= 10 - < 20 %
ethyl benzene	100-41-4	>= 5 - < 10 %

**SECTION 16. OTHER INFORMATION****Further information****NFPA 704:****HMIS® IV:**

<b>HEALTH</b>	*	<b>3</b>
<b>FLAMMABILITY</b>		<b>2</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of other abbreviations**

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	: USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	: 8-hour, time-weighted average
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	: 8-hour time weighted average
OSHA P0 / STEL	: Short-term exposure limit
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-2 / TWA	: 8-hour time weighted average
OSHA Z-2 / CEIL	: Acceptable ceiling concentration
OSHA Z-2 / Peak	: Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation,

**TILT**

Version 2.0	Revision Date: 04/03/2023	SDS Number: S11303321	This version replaces all previous versions.
----------------	------------------------------	--------------------------	--

and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 04/03/2023

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8