according to the OSHA Hazard Communication Standard



Turflon® Ester Ultra

Version Revision Date: SDS Number: Date of last issue: 07/31/2023 1.2 10/11/2023 800080004590 Date of first issue: 03/31/2022

Corteva Agriscience™ encourages you and expects you to read and understand the entire SDS as there is important information throughout the document. This SDS provides users with information relating to the protection of human health and safety at the workplace, protection of the environment and supports emergency response. Product users and applicators should primarily refer to the product label attached to or accompanying the product container. This Safety Data Sheet adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

SECTION 1. IDENTIFICATION

Product name : Turflon® Ester Ultra

Manufacturer or supplier's details

COMPANY IDENTIFICATION

Manufacturer/importer : CORTEVA AGRISCIENCE LLC

9330 ZIONSVILLE RD

INDIANAPOLIS, IN, 46268-1053

UNITED STATES

Customer Information

Number

: 1-800-258-3033

E-mail address : customerinformation@corteva.com

Emergency telephone : INFOTRAC (CONTRACT 84224).

+1 800-992-5994 or +1 317-337-6009

Recommended use of the chemical and restrictions on use

Recommended use : End use herbicide product

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization : Sub-category 1B

- repeated exposure

Specific target organ toxicity : Category 2 (Kidney)

GHS label elements

according to the OSHA Hazard Communication Standard



Turflon® Ester Ultra

Version Revision Date: SDS Number: Date of last issue: 07/31/2023 1.2 10/11/2023 800080004590 Date of first issue: 03/31/2022

Hazard pictograms





Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.

H373 May cause damage to organs (Kidney) through prolonged

or repeated exposure.

Precautionary Statements : Prevention:

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P314 Get medical advice/ attention if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Triclopyr-2-butoxyethyl ester	64700-56-7	60.45
Balance	Not Assigned	>= 30 - < 40

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled : Move person to fresh air. If person is not breathing, call an

emergency responder or ambulance, then give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask etc). Call a poison control center or doctor for treatment

advice.

In case of skin contact : Take off contaminated clothing. Wash skin with soap and

plenty of water for 15-20 minutes. Call a poison control center

according to the OSHA Hazard Communication Standard



Turflon® Ester Ultra

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/31/2023

 1.2
 10/11/2023
 800080004590
 Date of first issue: 03/31/2022

or doctor for treatment advice.

Wash clothing before reuse. Shoes and other leather items which cannot be decontaminated should be disposed of

properly.

In case of eye contact : Hold eyes open and rinse slowly and gently with water for 15-

20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eyes. Call a poison control

center or doctor for treatment advice.

If swallowed : Call a poison control center or doctor immediately for treat-

ment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison

control center or doctor.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

None known.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing (chemical re-

sistant gloves, splash protection).

If potential for exposure exists refer to Section 8 for specific

personal protective equipment.

Notes to physician : No specific antidote.

Treatment of exposure should be directed at the control of

symptoms and the clinical condition of the patient.

Have the Safety Data Sheet, and if available, the product container or label with you when calling a poison control center or

doctor, or going for treatment.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Do not use direct water stream.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health. Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod-

ucts

During a fire, smoke may contain the original material in addition to combustion products of varying composition which may

be toxic and/or irritating.

Combustion products may include and are not limited to:

Nitrogen oxides (NOx)

according to the OSHA Hazard Communication Standard



Turflon® Ester Ultra

Version Revision Date: SDS Number: Date of last issue: 07/31/2023 1.2 10/11/2023 800080004590 Date of first issue: 03/31/2022

Hydrogen chloride gas

Carbon oxides

Specific extinguishing meth-

ods

Remove undamaged containers from fire area if it is safe to do

SO

Evacuate area.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions

If the product contaminates rivers and lakes or drains inform

respective authorities.

Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Prevent from entering into soil, ditches, sewers, underwater.

See Section 12, Ecological Information.

Methods and materials for containment and cleaning up

Clean up remaining materials from spill with suitable absorb-

ant.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, recovered material should be stored in a vented container.

The vent must prevent the ingress of water as further reaction with spilled materials can take place which could lead to over-

pressurization of the container.

Keep in suitable, closed containers for disposal. Wipe up with absorbent material (e.g. cloth, fleece). Neutralize with chalk, alkali solution or ammonia.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

according to the OSHA Hazard Communication Standard



Turflon® Ester Ultra

Version Revision Date: SDS Number: Date of last issue: 07/31/2023 1.2 10/11/2023 800080004590 Date of first issue: 03/31/2022

See Section 13, Disposal Considerations, for additional infor-

mation.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Persons susceptible to skin sensitization problems or asthma,

allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Handle in accordance with good industrial hygiene and safety

practice.

Avoid exposure - obtain special instructions before use. Smoking, eating and drinking should be prohibited in the ap-

plication area.

Do not get on skin or clothing. Avoid inhalation of vapor or mist.

Do not swallow.

Avoid contact with eyes.

Take care to prevent spills, waste and minimize release to the

environment.

Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Conditions for safe storage : Store in a closed container.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store near acids.

Strong oxidizing agents

Packaging material : Unsuitable material: None known.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parameters / Permissible	Basis
		exposure)	concentration	
Triclopyr-2-butoxyethyl ester	64700-56-7	TWA	2 mg/m3	Dow IHG

Engineering measures

Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations.

Personal protective equipment

Respiratory protection : Respiratory protection should be worn when there is a poten-

tial to exceed the exposure limit requirements or guidelines.

according to the OSHA Hazard Communication Standard



Turflon® Ester Ultra

Version Revision Date: SDS Number: Date of last issue: 07/31/2023 1.2 10/11/2023 800080004590 Date of first issue: 03/31/2022

If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator.

Hand protection

Remarks : Use gloves chemically resistant to this material when pro-

longed or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Butyl rubber. Chlorinated polyethylene. Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reac-

tions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Eye protection : Use safety glasses (with side shields).

Skin and body protection : Use protective clothing chemically resistant to this material.

Selection of specific items such as face shield, boots, apron,

or full body suit will depend on the task.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid.

Color : Yellow

Odor : Mild

Odor Threshold : No data available

pH : 3.36 (73 °F / 23 °C)

Concentration: 1 %
Method: pH Electrode
(1% aqueous suspension)

Melting point/range : Not applicable

according to the OSHA Hazard Communication Standard



Turflon® Ester Ultra

Version Revision Date: SDS Number: Date of last issue: 07/31/2023 1.2 10/11/2023 800080004590 Date of first issue: 03/31/2022

Freezing point No data available

Boiling point/boiling range : No data available

Flash point : $> 212 \,^{\circ}\text{F} / > 100 \,^{\circ}\text{C}$

Method: Pensky-Martens Closed Cup ASTM D 93, closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : 1.11 g/cm3 (68 °F / 20 °C)

Method: Digital density meter

Solubility(ies)

Water solubility : emulsifies

Autoignition temperature : > 617 °F / > 325 °C

Viscosity

Viscosity, dynamic : 23.4 mPa.s (68 °F / 20 °C)

10.8 mPa.s (104 °F / 40 °C)

Explosive properties : No

Oxidizing properties : No significant increase (>5C) in temperature.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : No decomposition if stored and applied as directed.

Stable under normal conditions.

Possibility of hazardous reac-

tions

Stable under recommended storage conditions.

No hazards to be specially mentioned.

according to the OSHA Hazard Communication Standard



Turflon® Ester Ultra

Version Revision Date: SDS Number: Date of last issue: 07/31/2023 1.2 10/11/2023 800080004590 Date of first issue: 03/31/2022

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

Decomposition products depend upon temperature, air supply

and the presence of other materials.

Decomposition products can include and are not limited to:

Nitrogen oxides (NOx) Hydrogen chloride gas

Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : LD50 (Rat, female): 3,200 mg/kg

Method: OECD Test Guideline 425

Acute inhalation toxicity : LC50 (Rat, male and female): > 5.05 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Symptoms: No deaths occurred at this concentration. Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat, male and female): > 5,000 mg/kg

Method: OECD Test Guideline 402

Components:

Triclopyr-2-butoxyethyl ester:

Acute oral toxicity : LD50 (Rat, male and female): 803 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.8 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Symptoms: The LC50 value is greater than the Maximum

Attainable Concentration.

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Symptoms: No deaths occurred at this concentration.

Assessment: The substance or mixture has no acute dermal

toxicity

according to the OSHA Hazard Communication Standard



Turflon® Ester Ultra

Version Revision Date: SDS Number: Date of last issue: 07/31/2023 1.2 10/11/2023 800080004590 Date of first issue: 03/31/2022

Skin corrosion/irritation

Product:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Mild skin irritation

Components:

Triclopyr-2-butoxyethyl ester:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Product:

Species : Rabbit

Result : No eye irritation

Components:

Triclopyr-2-butoxyethyl ester:

Species : Rabbit

Result : No eye irritation

Respiratory or skin sensitization

Product:

Test Type : Local lymph node assay (LLNA)

Species : Mouse

Result : The product is a skin sensitizer, sub-category 1B.

Components:

Triclopyr-2-butoxyethyl ester:

Species : Guinea pig

Assessment : The product is a skin sensitizer, sub-category 1B.

Germ cell mutagenicity

Components:

Triclopyr-2-butoxyethyl ester:

Germ cell mutagenicity - : In vitro genetic toxicity studies were negative., Animal genetic

Assessment toxicity studies were negative.

according to the OSHA Hazard Communication Standard



Turflon® Ester Ultra

Version Revision Date: SDS Number: Date of last issue: 07/31/2023 1.2 10/11/2023 800080004590 Date of first issue: 03/31/2022

Carcinogenicity

Components:

Triclopyr-2-butoxyethyl ester:

Carcinogenicity - Assess-

ment

For similar active ingredient(s)., Triclopyr., Did not cause cancer in laboratory animals.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Components:

Triclopyr-2-butoxyethyl ester:

Reproductive toxicity - As-

sessment

For similar active ingredient(s)., Triclopyr., In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals. Has been toxic to the fetus in laboratory animals at doses toxic to the mother., Did not cause birth defects in laboratory animals.

STOT-single exposure

Product:

Assessment : Evaluation of available data suggests that this material is not

an STOT-SE toxicant.

Components:

Triclopyr-2-butoxyethyl ester:

Assessment : Evaluation of available data suggests that this material is not

an STOT-SE toxicant.

STOT-repeated exposure

Components:

Triclopyr-2-butoxyethyl ester:

Target Organs : Kidney

Assessment : May cause damage to organs through prolonged or repeated

exposure.

according to the OSHA Hazard Communication Standard



Turflon® Ester Ultra

Version Revision Date: SDS Number: Date of last issue: 07/31/2023 1.2 10/11/2023 800080004590 Date of first issue: 03/31/2022

Aspiration toxicity

Product:

Based on available information, aspiration hazard could not be determined.

Components:

Triclopyr-2-butoxyethyl ester:

Based on physical properties, not likely to be an aspiration hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 0.44 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203 or Equivalent

Remarks: For similar material(s):

LC50 (Oncorhynchus mykiss (rainbow trout)): 0.984 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203 or Equivalent

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.35 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202 or Equivalent

Remarks: For similar material(s):

Toxicity to algae/aquatic

plants

: EbC50 (Pseudokirchneriella subcapitata (green algae)): 11

mg/l

End point: Biomass Exposure time: 72 h

Method: OECD Test Guideline 201 or Equivalent

Remarks: For similar material(s):

Toxicity to terrestrial organ-

isms

oral LD50 (Colinus virginianus (Bobwhite quail)): 1,350 mg/kg

Remarks: Based on information for a similar material:

Components:

Triclopyr-2-butoxyethyl ester:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 0.36 mg/l

Exposure time: 96 h

Test Type: flow-through test

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 2.9 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 3.00

according to the OSHA Hazard Communication Standard



Turflon® Ester Ultra

Version Revision Date: SDS Number: Date of last issue: 07/31/2023 1.2 10/11/2023 800080004590 Date of first issue: 03/31/2022

plants mg/l

End point: Growth rate inhibition

Exposure time: 96 h

Method: OECD Test Guideline 201

ErC50 (Myriophyllum spicatum): 0.0473 mg/l

Exposure time: 14 d

NOEC (Myriophyllum spicatum): 0.00722 mg/l

Exposure time: 14 d

M-Factor (Acute aquatic tox-

icity)

10

Toxicity to fish (Chronic tox-

icity)

NOEC (Rainbow trout (Oncorhynchus mykiss)): 0.0263 mg/l

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 1.6 mg/l

End point: number of offspring

Exposure time: 21 d

LOEC (Daphnia magna (Water flea)): 5.1 mg/l

End point: number of offspring

Exposure time: 21 d

MATC (Maximum Acceptable Toxicant Level) (Daphnia

magna (Water flea)): 2.9 mg/l End point: number of offspring

Exposure time: 21 d

M-Factor (Chronic aquatic

toxicity)

10

Toxicity to soil dwelling or-

ganisms

LC50 (Eisenia fetida (earthworms)): > 1,042 mg/kg

Exposure time: 14 d

Toxicity to terrestrial organ-

isms

oral LD50 (Colinus virginianus (Bobwhite quail)): 735 mg/kg

bodyweight.

Exposure time: 21 d

dietary LC50 (Colinus virginianus (Bobwhite quail)): 1890

mg/kg diet.

Exposure time: 8 d

oral LD50 (Apis mellifera (bees)): > 110 μg/bee

Exposure time: 48 h End point: mortality

contact LD50 (Apis mellifera (bees)): > 100 µg/bee

Exposure time: 48 h End point: mortality

according to the OSHA Hazard Communication Standard



Turflon® Ester Ultra

Version Revision Date: SDS Number: Date of last issue: 07/31/2023 10/11/2023 800080004590 Date of first issue: 03/31/2022

Persistence and degradability

Components:

Triclopyr-2-butoxyethyl ester:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 18 % Exposure time: 28 d

Method: OECD Test Guideline 301B or Equivalent

Remarks: 10-day Window: Fail

Biochemical Oxygen De-

mand (BOD)

0.004 kg/kg

ThOD : 1.39 kg/kg

Stability in water : Test Type: Hydrolysis

Degradation half life (half-life): 8.7 d (25 °C) pH: 7

Photodegradation : Rate constant: 2.3E-11 cm3/s

Method: Estimated.

Bioaccumulative potential

Components:

Triclopyr-2-butoxyethyl ester:

Bioaccumulation : Species: Fish

Bioconcentration factor (BCF): 110

Partition coefficient: n-

octanol/water

log Pow: 4.62

pH: 7

Remarks: Bioconcentration potential is moderate (BCF be-

tween 100 and 3000 or Log Pow between 3 and 5).

Balance:

Partition coefficient: n-

octanol/water

Remarks: No relevant data found.

Mobility in soil

Components:

Triclopyr-2-butoxyethyl ester:

Distribution among environ-

mental compartments

Remarks: Calculation of meaningful sorption data was not

possible due to very rapid degradation in the soil.

For the degradation product:

Triclopyr.

Potential for mobility in soil is very high (Koc between 0 and

50).

Stability in soil : Test Type: aerobic degradation

Dissipation time: 144 - 1,248 h

according to the OSHA Hazard Communication Standard



Turflon® Ester Ultra

Version Revision Date: SDS Number: Date of last issue: 07/31/2023 1.2 10/11/2023 800080004590 Date of first issue: 03/31/2022

Balance:

Distribution among environ-

mental compartments

Remarks: No relevant data found.

Other adverse effects

Components:

Triclopyr-2-butoxyethyl ester:

Results of PBT and vPvB

assessment

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be

very persistent and very bioaccumulating (vPvB).

Ozone-Depletion Potential : Remarks: This substance is not on the Montreal Protocol list

of substances that deplete the ozone layer.

Balance:

Results of PBT and vPvB

assessment

This substance has not been assessed for persistence, bioac-

cumulation and toxicity (PBT).

Ozone-Depletion Potential : Remarks: This substance is not on the Montreal Protocol list

of substances that deplete the ozone layer.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : If wastes and/or containers cannot be disposed of according

to the product label directions, disposal of this material must be in accordance with your local or area regulatory authorities. This information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regu-

lations.

If the material as supplied becomes a waste, follow all appli-

cable regional, national and local laws.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

according to the OSHA Hazard Communication Standard



Turflon® Ester Ultra

Version Revision Date: SDS Number: Date of last issue: 07/31/2023 1.2 10/11/2023 800080004590 Date of first issue: 03/31/2022

(Triclopyr-2-butoxyethyl ester)

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(Triclopyr-2-butoxyethyl ester)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo

aircraft)

Packing instruction (passen: 964

ger aircraft)

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

964

(Triclopyr-2-butoxyethyl ester)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A

EmS Code : F-A, S-F

Marine pollutant : yes(Triclopyr-2-butoxyethyl ester)

Remarks : Stowage category A

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR Road

Not regulated as a dangerous good

Further information

Marine Pollutants assigned UN number 3077 and 3082 in single or combination packaging containing a net quantity per single or inner packaging of 5L or less for liquids or having a net mass per single or inner packaging of 5 KG or less for solids may be transported as non-dangerous goods as provided in section 2.10.2.7 of IMDG code, IATA Special provision A197, and ADR/RID special provision 375.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Respiratory or skin sensitization

Specific target organ toxicity (single or repeated exposure)

according to the OSHA Hazard Communication Standard



Turflon® Ester Ultra

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/31/2023

 1.2
 10/11/2023
 800080004590
 Date of first issue: 03/31/2022

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

Triclopyr-2- 64700-56-7 >= 50 - < 70 %

butoxyethyl ester

2-butoxyethanol 111-76-2 >= 0.1 - < 1 %

2-Butoxyethyl 5330-17-6 >= 0.1 - < 1 %

Chloroacetate

US State Regulations

Pennsylvania Right To Know

Triclopyr-2-butoxyethyl ester 64700-56-7

The ingredients of this product are reported in the following inventories:

TSCA : Product contains substance(s) not listed on TSCA inventory.

TSCA list

The following substance(s) is/are subject to a Significant New Use Rule:

Triclopyr Ethyl Ester: 3,5,6-Trichloro- 60825-27-6 See 40 CFR § 721.8775; Final Rule

2-pyridinyloxyacetic acid, ethyl ester

No substances are subject to TSCA 12(b) export notification requirements.

Federal Insecticide, Fungicide and Rodenticide Act

EPA Registration Number : 62719-566

This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label:

CAUTION

Causes moderate eye irritation

Harmful if swallowed

Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

SECTION 16. OTHER INFORMATION

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

according to the OSHA Hazard Communication Standard



Turflon® Ester Ultra

Version Revision Date: SDS Number: Date of last issue: 07/31/2023 1.2 10/11/2023 800080004590 Date of first issue: 03/31/2022

Full text of other abbreviations

Dow IHG : Dow Industrial Hygiene Guideline Dow IHG / TWA : Time Weighted Average (TWA):

ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; ASTM -American Society for the Testing of Materials; ECx - Concentration associated with x% response; EmS - Emergency Schedule; ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - not otherwise specified; NOEC - Non-Observed Effective Concentration; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; (Q)SAR - (Quantitative) Structure Activity Relationship; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SDS - Safety Data Sheet; UN -United Nations. CFR - Code of Federal Regulations. IARC - International Agency for Research on Cancer. IATA-DGR - International Air Transport Association Dangerous Goods Regulations. OSHA - Occupational Safety and Health Administration. RCRA - Resource Conservation and Recovery Act. RQ - Reportable Quantity. SARA - Superfund Amendments and Reauthorization Act. TSCA - Toxic Substances Control Act.

Revision Date : 10/11/2023

Product code: GF-1529

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN