

# Granular Humic CA

## 0-0-10

### GUARANTEED ANALYSIS

Soluble Potash (K<sub>2</sub>O).....10.00%

Derived from Potassium Hydroxide.

### ALSO CONTAINS NON-PLANT FOOD INGREDIENT:

67.00% Humic Acids derived from Sub-Bituminous Coals.

F3445

### GENERAL INFORMATION

Granular Humic CA dry granules are extracted, refined, water-soluble humic acids that may aid in the uptake of micronutrients. This product can be blended with most dry fertilizers, including urea blends, and may be applied to most crops.

### DIRECTIONS FOR USE

**SOIL:** Broadcast, band, or prepare seed or transplant bed with 1-20 pounds per acre with dry fertilizer program. If applying with seed or in-season, incorporate with water or tillage. Multiple applications can be beneficial.

**SEEDING:** Band or broadcast 1-5 pounds with seed on cereal crops at planting.

**COMPATIBILITY:** Granular Humic CA is formulated to be mixed with most dry blends. Do not mix with fertilizers containing calcium or solution with low pH.

Proper mixing procedure:

1. Add all dry NPK and micros to blender
2. Add desired rate of Granular Humic CA
3. Blend until homogenous

In areas of high humidity or when adding AMS/urea blends, use of a drying agent is recommended.

For specialized uses, contact your local agricultural representative.

### PRECAUTIONARY STATEMENTS

#### KEEP OUT OF REACH OF CHILDREN

Based on currently available data, this product is not classified as a GHS hazardous substance. However, observe good industrial hygiene practices. Wash hands after handling. Refer to the Safety Data Sheet if first aid instructions are needed.

**STORAGE AND DISPOSAL:** Do not contaminate water, food or feed by storage, disposal or cleaning of equipment. Store in original container only and keep tightly sealed when not in use. Store away from incompatible materials. Dispose of contents/container in accordance with federal, state and local regulations.

#### LIMITATION OF WARRANTY AND LIABILITY

To access Red Zone Technologies' warranty statement, please go to [rztproducts.com/warranty](http://rztproducts.com/warranty).

All trademarks, service marks, trade names, trade dress, product names and logos appearing on this label are the property of their respective owners.

RZT232607



RED ZONE TECHNOLOGIES  
PO BOX 5471, FRESNO, CA 93755

NET WEIGHT: 55 POUNDS (25 kg)