Landmark

Provides Long Lasting Dense Foam

KEEP OUT OF REACH OF CHILDREN

WARNING

READ ENTIRE LABEL BEFORE USING

GHS CLASSIFICATIONS

Health - Acute Toxicity (Oral), Category 5 Skin Irritation, Category 3 Eye Irritation, Category 2A

GHS HAZARD STATEMENTS

May be harmful if swallowed. Causes serious eye irritation. Causes mild skin irritation.

PRECAUTIONARY STATEMENTS

Avoid contact with skin, eyes, and clothing. Avoid inhalation of spray mist. Wash thoroughly with soap and water after handling. Read and follow all precautionary statements on the accompanying pesticide label(s).

FIRST AID CALL A POISON CONTROL CENTER OR DOCTOR IF YOU FEEL UNWELL

If in eyes: Hold eyes open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.

If on skin or clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

If swallowed: Immediately call a poison control center or doctor for treatment advice. Do not induce vomiting unless told to do so by the poison control center or doctor. Have person sip a glass of water if able to swallow. Do not give anything by mouth to an unconscious person.

If Inhaled: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible.

PRINCIPAL FUNCTIONING AGENTS Surfactant blend, solvents and foam boosting additives 100% TOTAL 100%

Components exempt from tolerance under 40CFR 180

GENERAL INFORMATION

LANDMARK is a long lasting foam that increases visibility of sprayer swaths to improve application accuracy in high winds and hard water conditions. LANDMARK is easy to mix and is compatible with foam dyes, antifreeze and cold water.

O DIRECTIONS FOR USE

LANDMARK mixes easily; best results can be obtained by adding the concentrate halfway into the filling of the foam tank with water.

MIXING INSTRUCTIONS SHAKE WELL OR RECIRCULATE BEFORE USE

■ RECOMMENDED RATES

Standard Rate: 100:1 ratio (1 gallon per 100 gallons) **Soft Water:** (<300 ppm hardness) 120:1 to 160:1 ratio **Hard Water:** (>1000 ppm hardness) 80:1 ratio

STORAGE AND DISPOSAL

Storage: Store between 45°F and 90°F. DO NOT FREEZE. Keep containers tightly closed. Store in original container. Do not allow water or other chemicals to be introduced into contents of container. Do not contaminate water sources with equipment wash water, spray disposal wastes or by cleaning of equipment. Do not store near feed or food products. Do not use or store near open flame.

Disposal: Do not reuse product containers. Triple rinse (or equivalent), then offer for recycling at an ACRC site (go to http:www.acrecycle.org/ for locations) or by reconditioning, or puncture and dispose of in a sanitary landfill or by other procedures approved by local, state, and federal regulations.

CONDITIONS OF SALE AND WARRANTY

The Directions for Use of this product are based on field use and tests. The directions are believed to be reliable and should be followed carefully. However, it is impossible to eliminate all risks inherently associated with the use of this product. Crop injury, ineffectiveness, or other unintended consequences may result because of such factors as weather conditions, presence of other materials, or the manner of use or application all of which are beyond the control of manufacturer or the Seller. All such risks shall be assumed by the Buyer. THE MANUFACTURER OR SELLER MAKES NO OTHER EXPRESSED OR IMPLIED WARRANTY OF FITNESS OR MERCHANTABILITY OF ANY OTHER EXPRESSED OR IMPLIED WARRANTY. IN NO CASE SHALL THE SELLER BE LIABLE FOR CONSEQUENTIAL, SPECIAL, OR INDIRECT DAMAGE RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT. The manufacturer and the Seller offer this product, and the Buyer and User accept it, subject to the foregoing Conditions of Sale and Warranty, which may be varied only by agreement in writing signed by a duly authorized representative of the manufacturer. 100614

