



GUARANTEED ANALYSIS

Total Nitrogen (N)	28.00%
2.40% Ammoniacal Nitrogen	
25.60% Urea Nitrogen*	
Available Phosphate (P ₂ O ₅)	4.00%
Soluble Potash (K ₂ O)	12.00%
Sulfur (S)	1.80%
1.80% Combined Sulfur (S)	
Iron (Fe)	4.00%

Derived from Ammonium Sulfate, Monoammonium Phosphate, Polymer Coated Urea, Urea, Muriate of Potash, and Iron Sulfate.

*16.80% Slowly available urea nitrogen from polymer coated urea.

F2544

DESCRIPTION

PERFECTION® LONG DRIVE™ is an economical high nitrogen blend utilizing a 7:1:3 nitrogen:phosphate:potash ratio with WIL-COTE II polymer coated urea. Great for spring and summer applications when long term results are required.

BENEFITS

- 16.80% controlled release urea nitrogen from WIL-COTE II polymer coated urea.
- 4.00% iron for quick green-up without surge growth.
- Uniquely formulated for high nitrogen requirement applications.

**POWERED BY
WIL-COTE
TECHNOLOGY®**

Nitrogen Release Gauge
Up to 14 weeks



DIRECTIONS FOR USE

APPLICATION INSTRUCTIONS

- For professional use on residential and commercial landscapes, golf courses, athletic fields, parks and sod farms.
- For best performance, apply to dry turfgrass and water after application.
- Do not apply directly to an impervious surface or to frozen ground.
- Keep away from pools, ponds and any bodies of water. Do not contaminate potable water.
- This product contains iron, which may cause staining. Keep off unwanted areas such as sidewalks, patios, fences, and painted areas. Sweep or blow any residual material on to treated areas after application.

RATE RECOMMENDATIONS

Use Sites		Nitrogen Rate / 1,000 sq. ft.	Amount of Product per 1,000 sq. ft.	Amount of Product per 100 sq. ft.	50 lb Bag Coverage (sq. ft.)
Turfgrass	Low	0.5 lb	1.79 lb		27,933
	Recommended	1 lb	3.57 lb		14,006
	High	1.5 lb	5.36 lb		9,328
Hydro-Seeding	Recommended	1 lb	3.57 lb		14,006
	High	1.5 lb	5.36 lb		9,328
Ornamentals	Recommended	1 lb	3.57 lb	5.7 oz	14,006

SPREADER SETTINGS (Based on 3.57 lb/1,000 sq. ft.)

AccuPro® 2000	1½ (12 ft. spread width)
Lesco Commercial	14½ (10 ft. spread width)
CBR II	5 (10 ft. spread width)
EarthWay®	14½ (12 ft. spread width)
Spyker® 7622	4.5 (12 ft. spread width)

Spreader settings are guidelines only. Spreaders should be checked for accuracy.

PRECAUTIONARY STATEMENTS

KEEP OUT OF REACH OF CHILDREN

Based on currently available data, this product is not classified as a GHS hazardous substance. However, observe good industrial hygiene practices. Wash hands after handling. Refer to the Safety Data Sheet if first aid instructions are needed.

STORAGE AND DISPOSAL: Do not contaminate water, food or feed by storage, disposal or cleaning of equipment. Store in original container only and keep tightly sealed when not in use. Store away from incompatible materials. Dispose of contents/container in accordance with federal, state and local regulations.

Information regarding the contents and levels of metals in this product is available on the Internet at <http://www.aapco.org/metals.html>

⚠ WARNING: Cancer and Reproductive Harm
www.P65Warnings.ca.gov

CONDITIONS OF SALE AND LIMITATION OF WARRANTY AND LIABILITY

NOTICE: Read the entire Directions for Use and Conditions of Sale and Limitation of Warranty and Liability before buying or using the product. If the terms are not acceptable, return the product at once, unopened, and the purchase price will be refunded.

The Directions for Use of the product should be followed carefully. It is impossible to eliminate all risks inherently associated with the use of this product. Crop injury, ineffectiveness, or other unintended consequences may result because of many different factors including, without limitation, manner of use or application, weather, combination with other products, or crop conditions. All such risks shall be assumed by Buyer and User, and Buyer and User agree to hold Manufacturer and Seller harmless from any claims relating to such factors.

Seller warrants that this product conforms to the chemical description on the label. EXCEPT FOR THIS WARRANTY, THE PRODUCT IS FURNISHED "AS-IS," AND NEITHER SELLER NOR MANUFACTURER MAKES ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THE SELECTION, PURCHASE OR USE OF THIS PRODUCT; SELLER AND MANUFACTURER SPECIFICALLY DISCLAIM ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Buyer and User accept all risks arising from any use of this product, including without limitation uses contrary to label instructions, under abnormal conditions, or under conditions not reasonably foreseeable to (or beyond the control of) Seller or Manufacturer.

To the extent permitted by law, neither Manufacturer nor Seller shall be liable for any incidental, consequential or special damages resulting from the use or handling of this product. THE EXCLUSIVE REMEDY OF THE BUYER OR USER, AND THE EXCLUSIVE LIABILITY OF MANUFACTURER AND SELLER, FOR ANY AND ALL CLAIMS, LOSSES, INJURIES OR DAMAGES (INCLUDING CLAIMS BASED ON BREACH OF WARRANTY, CONTRACT, NEGLIGENCE, TORT, STRICT LIABILITY OR OTHERWISE) RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT, SHALL BE THE RETURN OF THE PURCHASE PRICE OF THIS PRODUCT, OR, AT THE ELECTION OF MANUFACTURER OR SELLER, THE REPLACEMENT OF THE PRODUCT.

These Conditions of Sale and Limitation of Warranty and Liability shall be interpreted in accordance with the laws of the State of California, excluding its conflicts of laws rules, and may not be amended by any oral or written agreement.

WILBUR-ELLIS logo, Powered by WIL-COTE Technology, and PERFECTION are registered trademarks, and PERFECTION logo and LONG DRIVE are trademarks of Wilbur-Ellis Company LLC. AccuPro is a registered trademark of The Brothill Company. EarthWay is a registered trademark of EarthWay Products, Inc. Spyker is a registered trademark of Brinly-Hardy Company.

Guaranteed by:
WILBUR-ELLIS COMPANY LLC
3300 South Parker Road, Suite 500
Aurora, CO 80014 (720) 306-6340



WILBUR-ELLIS.

NET WEIGHT: 50 POUNDS (22.68 kg)